



NCR EasyPoint™ Advantage

Innovation with Experience



- Ultra Compact, Light-Weight Design
- Flexible Mounting Options
- Rugged Construction
- Superior Serviceability

The NCR EasyPoint Advantage is an all-in-one kiosk with a sleek compact design. Built on industry standards, the kiosk supports both Web-based applications and standard Microsoft® Windows® applications and delivers motion picture quality video and multimedia. The flexible kiosk can be configured to meet your business needs.

Good Things Come in Small Packages

With a depth of less than 3 inches and a weight of less than 15 pounds, the EasyPoint Advantage provides the ultimate versatility. Standard VESA mounting offers a variety of ready-to-use mounting options allowing you to place the kiosk wherever you need it. The small form factor does not mean limited functionality. The kiosk allows superior connectivity with four USB ports, four serial ports, and a parallel port.



NCR offers a full range kiosk of peripherals with packaging and mounting options to provide you with a comprehensive solution for your self-service needs. This combination of performance, packaging and mounting is intended to enable easy installation virtually anywhere, including a tabletop, shelf, pole, wall or pedestal.

Robust and Durable for Years of Dependable Service

To ensure the highest quality, reliability and safety, the EasyPoint Advantage undergoes comprehensive environmental and compatibility testing. Spills and retail abuse are no problem with the NEMA 4/IP 65 dust and water proof display.

Designed for Ease of Service

The EasyPoint Advantage provides a secure kiosk design while allowing easy service. Through the use of a user-friendly “sled,” the EasyPoint Advantage makes all main board components available for straightforward visual inspection and replacement in a fraction of the time necessary for other solutions. Time is money, and the service features unique to the EasyPoint Advantage ensure maximum availability.

NCR EasyPoint™

Advantage



Technical Specifications

- 15" TFT LCD (350 nit) 1024 x 768
- 17" TFT LCD (420 nit) 1280x764
- Resistive touch screen (6 Wire) or Surface Acoustic Wave (SAW)
- Integrated stereo speakers
- P4 Celeron® M 1.3 GHz processor
- 512MB – 2GB RAM (SO-DIMM)
- 40GB or 80GB Hard Disk Drive
- VESA mount
- 4 USB 2.0 ports
- 4 RS-232 ports (RJ45 Connectors) (2 powered 5v/12v)
- 10/100-BaseT Ethernet
- Integrated infrared motion sensor
- Parallel port(25 Pin), cash drawer port (RJ-11)
- Secured volume and brightness controls
- Integrated stereo speakers
- Audio in / out

OS Support:

- Microsoft® Windows® XP Pro, XPe, WEPOS, Linux (NLPOS 9)

Options:

- Omni Directional scanner
- Wall, pole and pedestal mounting
- 3-Track ISO magnetic stripe reader or JIS MSR
- Mini PCI wireless 802.11 a/b/g
- Self-service printer (80mm, 112mm) or Full Page Printer
- Compact Flash
- Integrated IRDA reader

Physical Specifications

- | | |
|----------------------------|----------------------------|
| • Core module with 15" LCD | • Core module with 17" LCD |
| - Height 13"/ 330 mm | - Height 14.6"/ 370 mm |
| - Depth 2.5"/ 65 mm | - Depth 2.7"/ 68 mm |
| - Width 15.5"/ 386mm | - Width 16.5"/ 419 mm |
| - Weight 11 lbs./4.99 kg | - Weight 14 lbs./6.35 kg |

Environmental Specifications

- Operating temperature: 32°F-104°F 0°C-40°C
- Electrical requirements
 - Universal power supply
 - 100-240v ~ 50/60Hz, 1.4A

For more information, visit www.ncr.com, call 866.431.7879, or email retail.contactus@ncr.com.

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions, and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR EasyPoint is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks, or service marks of their respective holders.

© 2007 NCR Corporation

Patents Pending

Printed in U.S.A.

EB5016-1207



www.ncr.com